LASER PRINTER MB2236ADWE

According to ISO 14025





Lexmark's innovative imaging solutions and technologies help customers worldwide print, secure and manage information with ease, efficiency and unmatched value. Lexmark simplifies the complex intersection of digital and printed information.

As part of the commitment to our customers, Lexmark performs Life Cycle Analysis on our products. The results of the LCA analysis continues to assist Lexmark in reducing the environmental impact of the hardware, software and services offered to our customers.

With a 1-GHz processor driving monochrome output up to 36 [34] pages per minute*, the compact Lexmark MB2236adwe MFP provides impressive performance and valuable extras. Standard features include Wi-Fi, scanning at up to 25 [23] pages per minute, and a front-panel USB port. Support for popular mobile printing apps takes care of users on the go, while the e-Task touch screen includes embedded workflow capabilities like Cloud Connector***. Easy to set up and simple to maintain, the MB2236adwe is ideal for 2-4-member workgroups. Lexmark-exclusive full-spectrum security is built in, and toner cartridges up to 6000 pages are available**.





Laser Printer MB2236adwe
Printers and multi-functional printing units


According to ISO 14025

This declaration is an environmental product declaration (EPD) in accordance with ISO 14025. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycle. Exclusions: EPDs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity.



EPDs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds — e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc. Accuracy of Results: EPDs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. Comparability: EPDs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or ar missing relevant environmental impacts. EPDs from different programs may not be comparable.

PROGRAM OPERATOR	UL Environment			
DECLARATION HOLDER	Lexmark			
DECLARATION NUMBER	4790060659.102.1			
DECLARED PRODUCT	Laser Printer MB2236adwe			
REFERENCE PCR		or preparing an environmental product declaration printing units (v2.0). UL Environment		
DATE OF ISSUE	December 15, 2021			
PERIOD OF VALIDITY	5 Years			
	Product definition			
	Information about basic material and	d the material's origin		
CONTENTS OF THE	Description of the product's manufacture			
CONTENTS OF THE DECLARATION	Indication of product processing			
DECLARATION	Information about the in-use conditions			
	Life cycle assessment results			
	Testing results and verifications			
The PCR review was conducted	1 hv:	UL Environment Review Panel		
The Fort Teview was conducted	a by.	Lise Laurin (Chairperson)		
		31 Leach Road; Kittery, Maine 03904; lise@earthshift.com		
This declaration was independently verified in accordance with ISO 14025 by Underwriters Laboratories		CooperMcC		
☐ INTERNAL		Cooper McCollum, UL Environment		
This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:		Thomas Storie		
	-	Thomas Gloria, Indust. Ecology Consultants		



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Product Description

Product Type	Mono Laser Printer
Printer Model	MB2236adwe
Maximum Print Speed	36 pages per minute
Intended use	primarily office
Range of applications	print images or text in mono onto paper or paper-like media
Product Lifetime	5 years
Introduction Date	1/29/2019
Product Specifications	https://www.lexmark.com/en_in/printer/14205/Lexmark-MB2236adwe
Functional Unit	The functional unit has been defined as a 1,000 page simplex job in accordance with the Energy Star Typical Energy Consumption test procedure and the reference Product Category Rule (PCR).
Scope of Validity / Applicability	The EPD is representative for the printer model MB2236adwe sold as a stand-alone unit. This EPD and the reference PCR are applicable for printer sale and use in the North American market. Lexmark cannot guarantee that comparisons with EPDs of competitive products will be valid.
Product Characterization	With monochrome output up to 36 [34] pages per minute*, the compact, high-performance and affordable Lexmark MB2236adw MFP also includes Wi-Fi, two-sided printing, scanning and fax. The printer product delivered to the customer consists of the printer, a power cord, printed setup instructions, a CD/DVD that includes the User Guide and Printer Drivers and an initial set of product supplies. The printer is delivered in packaging that can be recycled locally and is not needed for product operation. Product supplies include toner cartridges, imaging kits and the fusing mechanism. The power supply is internal to the product and the imaging kit and fusing mechanism are installed at the factory. Only the toner cartridges must be installed by the customer. The printer can be setup by the customer without outside assistance.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Technical Data

Product Specifications	Lexmark MB2236adwe			
Printing				
Display	2.8 inch (7.2 cm) LCD touch panel			
Print Speed	Up to: Black: 36 ppm 1 (Letter)			
Time to First Page	As fast as: Black: 7.9 seconds			
Print Resolution	Black: 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi, 1200 IQ (1200 x 600 dpi)			
Memory	Standard: 512 MB / Maximum: 512 MB			
Hard Disk	Not Available			
Recommended Monthly Page Volume	250 - 2500 pages ²			
Maximum Monthly Duty Cycle	Up to: 30000 pages per month ³			
Copying				
Copy Speed	Up to: Black: 36 cpm ¹ (Letter)			
Time to First Copy	As fast as: Black: 8.5 seconds			
Scanning				
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex			
A4/Ltr Simplex Scan Speed	Up to: Black: 23 / 25 sides per minute / Color: 7 / 8 sides per minute			
ADF Paper Input Capacity	Up to: 50 pages 20 lb or 75 gsm bond			
Faxing				
Modem Speed	Max is 33,600 bps, V.34 Half-Duplex Kbps			
Supplies ⁴				
Laser Cartridge Yields	up to: 1,200 ⁵ -page Cartridge / up to: 3,000 ⁵ -page High Yield Cartridge / up to: 6,000 ⁶ -page Extra High Yield Cartridge			
Imaging Unit Estimated Yield	Up to: 12000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage ⁶			
Cartridge(s) Shipping with Product	700 ⁵ -page Black Return Program Toner Cartridges			
Paper Handling				
Included Paper Handling	Integrated Duplex, Single-Sheet Manual Feed, 150-Sheet Output Bin, 250-Sheet Input			
Paper Input Capacity	Up to: Standard: 251 pages 20 lb or 75 gsm bond / Maximum: 251 pages 20 lb or 75 gsm bond			
Paper Output Capacity	Up to: Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond			
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide			
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope			
General Information ⁷				
Standard Ports	Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11b/g/n Wireless, USB 2.0 Specification Hi-Speed Certified (Type B), Ethernet 10/100BaseTX (RJ-45)			
Noise Level	Operating: 52 dBA (Print) / 55 dBA (Copy) / 52 dBA (Scan)			
Specified Operating Environment	Temperature: 10 to 32::C (50 to 90::F) / Altitude: 0 - 2896 Meters (9,500 Feet) / Humidity: 15 to 80% Relative Humidity			
Limited Warranty	See Statement of Limited Warranty: 1-Year Advanced Exchange			
Size / Weight	H x W x D: 13.9 x 16.4 x 14.2 in. / 22 lb.			
ENERGY STAR Typical Electricity Consumption	TEC: 0.53 kilowatt-hours per week			

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

System Boundary

The study considers all phases of the life cycle, as shown below.




Figure 1: System Boundaries

Declaration of Basic Materials

The printer consist of mechanical, electromechanical, and electronic components. Its material composition can be described using the basic material fractions given below. Please note that the category 'Electronics' also includes all wiring.

Material	Mass (kg)
Plastics (recyclable)	6.01
Plastics (non-recyclable)	0.0834
Ferrous Metals	3.75
Aluminum	0.0502
Copper	0
Glass	0.717
Electronics	0.827
Other Materials	0.0441

Table 1: Basic Material Declaration

Product Supply Chain

The printer is manufactured and assembled in Southeast China. The cartridges for the North American market are manufactured and assembled in Juarez, Mexico.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Life Cycle Assessment Results

The following sections describe the printer's potential environmental impacts over the full printer life cycle. These represent the typical impacts for an average system sold in the North American market. All impacts are presented per functional unit of printing 1,000 images of the reference standard.

Manufacturing Material and Resources Inventory

Table 2 displays the use of material resources (kg) and of non-renewable as well as renewable primary energy demand necessary for printer manufacturing, but excludes other life cycle stages of the printer (cradle-to-gate). Likewise, material and energy consumption associated with printer packaging, cartridges, and paper is excluded here.

Use of Material Resources [kg]			
Non-Renewable	686		
Renewable (excl. water)	1.11E003		
Water	1.85E013		
Use of Non-Renewable Prima	ry Energy [MJ]		
Crude Oil	323		
Hard Coal	687		
Lignite	29.7		
Natural Gas	571		
Uranium	85.6		
Use of Renewable Primary Energy [MJ]			
Biomass	2.76E-005		
Geothermal	1.02		
Solar	86.1		
Wind	45.9		
Hydropower	72.9		

Table 2: Use of Material and Energy Resources for Printer Manufacturing (Cradle-to-Gate)

Energy Consumption During Utilization

Based on the EnergyStar Typical Energy Consumption (TEC) test methodology, the printer is expected to have the following power consumption for an assumed average job load.

	Per 1,000 page	Per product lifetime
Energy Consumption During Utilization [kWh]	0.175	146

Table 3: At-wall power consumption during utilization



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Life Cycle Impact Assessment

The following provides an overview of the potential printer life cycle impacts with emissions classified and characterized to standard environmental impact metrics using the ReCiPe 2016 Hierarchist (H) midpoint characterization factors (v1.1).

Note that the mineral resource depletion results do not include any contributions from the paper life cycle as the AF&PA report does not allow for the conversion to ReCiPe 2016.

Ecotoxicity and human health are not included in this study, as per the PCR, due to their respective uncertainties.

LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

	per 1000 pages	per 1000 pages	per printer	per printer
	including paper	excluding paper	lifetime	lifetime
			including paper	excluding paper
G lobal Warming Potential [kg CO2 eq.]	9.68E00	3.30E00	8.05E03	2.74E03
Ozone Depletion Potential [kg CFC-11 eq.]	1.22E-06	1.22E-06	1.01E-03	1.01E-03
Acidification Potential [kg SO2 eq.]	6.39E-03	6.39E-03	5.32E00	5.32E00
Eutrophication Potential [kg P eq.]	3.44E-05	3.44E-05	2.86E-02	2.86E-02
Fossil Fuel Depletion Potential [kg oil eq.]	1.07E00	1.07E00	8.93E02	8.93E02
Mineral Resource Depletion Potential [kg Cu eq.]	2.09E-02	2.09E-02	1.74E01	1.74E01

Table 3: Summary of Life Cycle Impact Assessment Results



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Interpretation of Results

Dominance Analysis

Due to the 5 year lifetime and the number of pages printed per day as established by the Energy Star Typical Energy Consumption test procedure, the use phase heavily dominates the life cycle impacts. The below tables and charts display the results of the dominance analysis for each impact category addressed in Table 3.

Global Warming Potential

				per printer lifetime excluding paper
Printer	1.36E-01	1.36E-01	1.13E02	1.13E02
Lexmark use phase <lc></lc>	9.54E00	3.16E00	7.94E03	2.63E03
Lexmark EoL phase <lc></lc>	1.16E-03	1.16E-03	9.68E-01	9.68E-01

Table 4: Fossil GWP100 dominance analysis [kg CO2 equiv]




Figure 1: Fossil GWP100 dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Ozone Depletion Potential

				per printer lifetime excluding paper
Printer	3.12E-08	3.12E-08	2.60E-05	2.60E-05
Lexmark use phase <lc></lc>	1.18E-06	1.18E-06	9.85E-04	9.85E-04
Lexmark EoL phase <lc></lc>	1.29E-10	1.29E-10	1.08E-07	1.08E-07

Table 5: ODP dominance analysis [kg CFC-11 equiv]




Figure 2: ODP dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Acidification Potential

				per printer lifetime excluding paper
Printer	8.20E-04	8.20E-04	6.82E-01	6.82E-01
Lexmark use phase <lc></lc>	5.57E-03	5.57E-03	4.64E00	4.64E00
Lexmark EoL phase <lc></lc>	2.86E-06	2.86E-06	2.38E-03	2.38E-03

Table 6: AP dominance analysis [kg SO₂ equiv]




Figure 3: AP dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Eutrophication Potential

				per printer lifetime excluding paper
Printer	6.13E-07	6.13E-07	5.10E-04	5.10E-04
Lexmark use phase <lc></lc>	3.38E-05	3.38E-05	2.81E-02	2.81E-02
Lexmark EoL phase <lc></lc>	6.03E-09	6.03E-09	5.01E-06	5.01E-06

Table 8: EP dominance analysis [kg P equiv]




Figure 4: EP dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Fossil Fuel Depletion Potential

				per printer lifetime excluding paper
Printer	4.76E-02	4.76E-02	3.96E01	3.96E01
Lexmark use phase <lc></lc>	1.03E00	1.03E00	8.53E02	8.53E02
Lexmark EoL phase <lc></lc>	3.91E-04	3.91E-04	3.25E-01	3.25E-01

Table 9: Fossil fuel depletion dominance analysis [kg oil equiv]




Figure 5: Fossil resource depletion dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Mineral Resource Depletion Potential

				per printer lifetime excluding paper
Printer	7.44E-03	7.44E-03	6.19E00	6.19E00
Lexmark use phase <lc></lc>	1.34E-02	1.34E-02	1.12E01	1.12E01
Lexmark EoL phase <lc></lc>	1.26E-05	1.26E-05	1.05E-02	1.05E-02

Table 10: Mineral resource depletion dominance analysis [MJ surplus]




Figure 6: Mineral resource depletion dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Primary Energy Demand from Renewable and Non-renewable Resources

				per printer lifetime excluding paper
Printer	2.29E00	2.29E00	1.90E03	1.90E03
Lexmark use phase <lc></lc>	9.34E01	4.70E01	7.77E04	3.91E04
Lexmark EoL phase <lc></lc>	1.78E-02	1.78E-02	1.48E01	1.48E01

Table 11: PED dominance analysis [MJ]




Figure 7: PED dominance analysis of the use phase



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Assumptions and Estimations

Assumptions and estimations follow the governing PCR on printing equipment. Full details are documented in the EPD's background report, which was provided for verification purposes alongside the EPD. The LCA results represent the specific printer model as sold in the North American market.

In line with the PCR, the model assumes a printer lifetime of five (5) years. The printer is modeled to print an average of 640 pages per day based on a maximum print speed of 36 images per minute. The printer further possesses an automatic mechanic duplexing feature.

Power consumption figures are based on Energy Star testing of the printer using the average job load described above. Consumables consumption is based on the market-average yield across all available cartridge capacities. In addition, market-average use of remanufactured cartridges is taken into account, as applicable.

Transportation distances to the end consumer are based on their points of origin and the population-weighted average distance to the 100 most populous cities in the continental US based on 2010 census data. The printer as well as replacement fuser kits and waste toner bottles are manufactured in China and shipped to the point of use from the distribution center near Memphis, TN, while the cartridges and the imaging unit are shipped from Ciudad Juarez, MX.

The LCI data for office paper is adopted from the uncoated, free sheet paper inventory developed by the American Forest & Paper Association (AF&PA). This paper dataset assumes that average office paper contains 4% recycled content. The mass of consumed paper is based on the US letter format and a surface weight of 75 g/m². The AF&PA data includes paper production, transportation, and End-of-Life treatment (72% recycling, 23% landfill, 5% incineration).

The End-of-Life treatment for the printer is based on the assumption that 66.7 % of the printers are returned to Lexmark for recycling, while the remainder is disposed of through local waste streams, where the metal fractions are assumed to be recycled and the remainder landfilled. The EoL cartridges are assumed to go to remanufacturing, recycling, and landfill in equal shares.

In accordance with the cut-off methodology prescribed by the governing PCR, materials sent to End-of-Life recycling are considered to cross the system boundary without any further transformation. Only the impacts associated with waste transportation and disposal are included in the results.

Description of Data and Period Under Consideration

All primary data is based on technical documentation and sales data accessed in 2021. All background data is taken from the GaBi 2021-10.5.1.124 Databases. No primary data is collected from the Original Equipment Manufacturer's manufacturing plant.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Data Quality

Manufacturing data of printers and consumables is based on a combination of Bills of Material and teardown analyses and is considered to be of overall high quality with low uncertainty. Distribution from printer manufacturing to the end consumer is representative of logistical data from Lexmark and best estimates of US average shipping distances, and is of moderate quality and high uncertainty.

Printer power consumption represents measured power consumed during printer operation in accordance with the use scenario outlined in the reference PCR and is of high quality and moderate uncertainty; actual print loads may differ. Toner cartridge use is based on expected yields based on the ISO test standards for cartridge use, and is of high quality and low uncertainty. Replacement rate for consumable parts is based on part design specifications, and is of high quality and moderate uncertainty.

The disposition of the printer and consumables at End-of-Life is based on best-available information by the respective experts at Lexmark. This data is of average quality and moderate uncertainty.

Background Data

All background datasets relevant to production, power generation, transportation, and material disposal were taken from the GaBi 2021-10.5.1.124 Databases.

The data used for office paper is based on the data developed for the American Forest & Paper Association (AF&PA) and is representative for average North American office paper production in 2010.

The additional use of third-party background data from industry associations (e.g., worldsteel) is documented in the background report. They represent the latest LCI data as available in the GaBi 2021-10.5.1.124 Databases.

Allocation and Methodological Principles

No significant allocations have been considered for the production of the printer. Allocation of production or use impacts across the various functions of a multi-function system is not included (i.e., allocation of production impacts to the provision of scanning services) and the impacts from all life cycle stages are considered within the system boundaries for the printing system.

Treatment of recycled or resold material is not considered in the body of the EPD, in accordance with the cut-off methodology required by the governing PCR.

A description of all of the methodological decisions made in modeling the life cycle impacts of office paper, including descriptions of the approach to modeling carbon sequestration and paper recycling, are described in the American Forestry & Paper Association's LCA report on printing and writing papers.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

Additional Environmental Information

As required by the governing PCR, the assessment of human toxicity and ecotoxicity shall be included in this additional information section. The following metrics, which are based on the scenario 'per printer lifetime including paper' can help identify toxicity hot spots, but decision-making should also consider an exposure assessment.

	USEtox - Ecotoxicity [CTUe]	USEtox - Human toxicity (cancer) [CTUh]	USEtox - Human toxicity (non- cancer) [CTUh]
Printer use - Cartridges/Toner	4.89E-01	3.59E-08	3.82E-09
Printer use - Distribution	1.19E-01	2.05E-10	4.97E-11
Printer Use - Energy	4.34E-02	4.57E-09	9.06E-11
Printer use - Maintenance	4.90 E0 0	2.41E-08	7.29E-09
Printer use - Packaging	2.60E-01	1.87E-08	1.46E-07
Printer use - Waste treatment	8.07E-02	1.76E-10	3.54E-11



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

References and Standards

EPA (2013) ENERGY STAR Program Requirements for Imaging Equipment – Test Method (Rev. Jun-2013) https://www.energystar.gov/sites/default/files/FINAL%20Version%202.0%20Imaging%20Equipment%20Program%20Requirements%20%28Rev%20Oct-2014%29 0.pdf

ISO (2006a) ISO 14025: Environmental labels and declarations — Type III environmental declarations — Principles and procedures. International Organization for Standardization. Geneva.

ISO (2006b) ISO 14040: Environmental management - Life cycle assessment — Principles and framework. International Organization for Standardization. Geneva.

ISO (2006c) ISO 14044: Environmental management - Life cycle assessment — Requirements and guidelines. International Organization for Standardization. Geneva.

NCASI (2010) Life Cycle Assessment of North American Printing and Writing Paper Products – Final Report. Prepared for the American Forest and Paper Association (AF&PA) and the Forest Products Association of Canada (FPAC) by the National Council for Air and Stream Improvement, Inc. Research Triangle Park, NC

thinkstep (2018) GaBi ts Product Sustainability Software. thinkstep AG, Leinfelden-Echterdingen. http://www.gabi-software.com

ReCiPe (2016) ReciPemethodology for Life Cycle Impact Assessment, version 1.1. Available at www.lcia-recipe.net

ULE (2018) Product Category Rules for preparing an environmental product declaration (EPD) for printers and multi-function printing units (v2.0). UL Environment. Washington, DC.



Laser Printer MB2236adwe Printers and multi-functional printing units

According to ISO 14025

Contact Information



Lexmark International, Inc. 740 W. New Circle Road Lexington, KY 40550

Tel: +1-859-232-2000



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

LCA/EPD Verifier:

Thomas P. Gloria, Ph. D. Industrial Ecology Consultants 35 Bracebridge Rd. Newton, MA 02459-1728 direct: 617.553.4929

email: t.gloria@industrial-ecology.com

Dr. Gloria is a certified Life Cycle Professional (LCACP) through the American Center for Life Cycle Assessment.



Laser Printer MB2236adwe
Printers and multi-functional printing units

According to ISO 14025

EU REACH (EC1907/2006) Substances of Very High Concern Disclosure



As a producer and supplier of articles Lexmark International, Inc. (Lexmark) has an obligation under Article 33 of the REACH Regulation (EC 1907/2006) to communicate information on Substances of Very High Concern (SVHC) present in a concentration greater than 0.1% weight by weight of that article.

A complete list of the candidate list of Substances of Very High Concern is found on the European Chemicals Agency web site: https://echa.europa.eu/candidate-list-table

Company:

Lexmark International Technology Hungária Kft. 8 Lechner Ödön fasor Millennium Tower III 1095 Budapest HUNGARY

Contact: Sustainability@lexmark.com

Lexmark declares that the products listed below are free of substances listed on the Candidate List of Substances of Very High Concern in a concentration above 0.1% weight by weight of that article as of the date of this disclosure except as listed below. Any substances listed below may be contained in articles above the threshold level. None are expected to be released from the component parts identified or to result in exposure during normal and expected use of Lexmark Imaging Equipment.

Scope of Disclosure:

All Printing and Imaging Equipment under the Lexmark Brand, including options and service parts

Substance Name	EC	CAS	Additional Information
	Number	Number	
1,2-dimethoxyethane	203-794-9	110-71-4	Coin cell battery electrolyte. Coin cell Battery found on main printed circuit board
Lead	231-100-4	7649-92-1	Found in some high temperature solder, some machining steels (shafts/roller), some Brass parts
2-(2H-benzotriazol-2-yl)-4,6- ditertpentylphenol (UV-328)	247-384-8	25973-55-1	found in the Display (Operator Panel)
Lead monoxide (lead oxide)	215-267-0	1317-36-8	leaded glass used in circuit boards, capacitors and ceramic heaters
Diboron trioxide	215-125-8	1303-86-2	found in ceramic heaters
Hexahydromethylphthalic anhydride	247-094-1	25550-51-0	Laser printhead adhesive
Cyclohexane-1,2-dicarboxylic anhydride	201-604-9	85-42-7	Laser printhead adhesive
1,3,5-Tris(oxiran-2-ylmethyl)- 1,3,5-triazinane-2,4,6-trione (TGIC)	219-514-3	2451-62-9	Laser printhead adhesive

Lexmark includes requirements for the disclosure of substances on the Candidate List of Substances of Very High Concern in agreements with our supply chain.

The statements in this disclosure are declared to be true and accurate to the knowledge of Lexmark as of the date of this disclosure. This disclosure is subject to change based on Lexmark receiving updated information from suppliers, changes to the product or the addition of new substances on the Candidate List of Substances of Very High Concern.

Christina Cullins

WW Materials Compliance Manager Corporate Sustainability Group

Lexmark International Inc.

Date of Disclosure: 31 December 2020