



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information * e-mail address	David DeVore Lexmark International 740 West New Circle Road, Bldg. 1 Lexington, KY 40550 david.devore@lexmark.com	L exmark
Internet site *	www.lexmark.com/TED and csr.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Single-function color laser device				
Commercial name *	Lexmark CS521dn				
Model number *	CS521dn				
Issue date *	June 19, 2018; Last revised on Dec 16th, 2019				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *	CS521dn		
Issue date *	June 19, 2018; Last revised on Dec 16th, 2019		Lexmark

Product	Product environmental attributes - Legal requirements						
Item		Yes	No	n.a.			
P1	Hazardous substances and preparations						
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	\boxtimes					
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.						
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.						
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).						
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	e 🔀					
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/weel (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.	X					
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 West New Circle Rd., Lexington, KY 40550						
P2	Batteries						
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)						
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See lega reference)						
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	\boxtimes					
P3	Conformity verification & Eco design (ErP)						
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): http://www.lexmark.com/en_us/about/regulatory-compliance/european-union-declaration-of-conformity.html						
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).						
	Required information is; given in item P15 or added to this document, available at (add URL): https://csr.lexmark.com/eu-regulations.php						
P4	Consumable materials						
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see legal reference and NOTE B1).						
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).	\square					
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there		$\overline{\Box}$				
	are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).						
P5	Product packaging						
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀					
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(sused (see legal reference).	s) 🔀					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montree Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀					
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	CS521dn	Logo	[™
Issue date *	June 19, 2018; Last revised on Dec 16th, 2019		Lexmark

	environmental attributes - Market requirements (See General NOTE GN below) Environmental conscious design	Require	ement	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No r	n.a.
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\boxtimes		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
	Material type: ABS Material type: PC+ABS Material type:			
P7.12	Insulation materials of external electrical cables are PVC free.		\boxtimes	
P7.13	Insulation materials of internal electrical cables are PVC free.		\boxtimes	
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.	d		
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low	,	\boxtimes	
	halogen as defined in IEC 61249-2-21. (See NOTE B2)			
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR40			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:			
	<u>Alt. 2:</u> Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: <i>FR16</i>			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR16, FR17, FR40, FR30+40			
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:			
	The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6):	\boxtimes		
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is <i>Up to 40</i> %. or b) The weight of recycled material is g.	l		

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Issue date		June 19,	Logo	Lex	ma	rk			
Product (oduct environmental attributes - Market requirements (continued) Requirement met								met
Item							Yes	No	n.a.
10111	Material and substance requirements (continued)							11.0.	
P7.21*	Biobased plastic material content is used in the product (See NOTE B7):								
	If YES; at least one of the two alternatives below shall be answered;								
	 a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is 								
	or b) The	weight of	the biobased plastic m	aterial is g.					
P7.22*			ee from mercury, i.e. le pecify: Number of lam		np. kimum mercury content pe	r lamp: mg	\boxtimes		
P8	Batteries								
P8.1*	Battery cl	nemical co	mposition: Lithium Ma	anganese Dioxide	(LiMnO2)				
P9	Energy o	onsumpti	ion (See NOTE B8)						
P9.1	For the p	roduct the	following power levels	or energy consum	ptions are reported:				
Energy mo	ode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard modes and test meth		nergy	
Sleep mod STAR® Op (OM) produ	perational I		W	W	W				
Standby/of ENERGY S	Standby/off mode for ENERGY STAR Operational Mode (OM) products		W	W	W				
TEC value TEC produ	for ENER		0.49 kWh/week	0.51 kWh/week	reek 0.48 kWh/week Energy Star I E V3.0				
(TEC= Typical Energy									
Printing			504 W	515 W	479 W	Corporate Standard			
Ready Mo	de 1		29.7 W	36.1 W	25.9 W	Energy Star I E V3.0			
Ready Mo	de 2		22.2 W	20.87 W	21.34 W	Energy Star I E V3.0)		
Sleep			1.27 W	1.29 W	1.27 W	Energy Star I E V3.0)		
Hibernate			<i>0.08</i> W	0.08 W	0.09 W	IEC 62301			
Off			0.08 W	0.08 W	0.09 W	IEC 62301			
External Po	ower Supp	ly Efficiend	cy Level (International	Efficiency Marking	Protocol) *:				\boxtimes
Print/Scan	Speed *	3	3 images per minute			ISO 24734			
Default tim	e to enter	energy sav	ve mode: 15 minutes			Energy Star I E V3.0)		
P9.2*	Information	on about th	ne energy save functio	n is provided with t	he product.		\boxtimes		
P10									
D10.1			Declared according to	ISO 9296 (See NC		sighted cound never le			
P10.1	Mode	IV	lode description		Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)				
	Idle		ldle / Ready		*3.1				
	Operation		Duplex Monochrome	_	* 6.4		·		
Other mode Simple Monochrome Printing 6.5									
	Measured according to: SISO 7779 ECMA-74 Other (only if not covered by ECMA-74)								
	1		U Other	(only if not covered	LOY LOWA-14)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nur	nber *	CS521dn						Logo				■ TM
Issue date	date * June 19, 2018; Last revised on Dec 16th, 2019						Lex	ma	rk			
Product	environ	mental attributes	- Market requirer	nents (cor	tinued)					Require	ment	met
Item			•	•						Yes	No	n.a.
		al emissions from										
P10.2*		rformed according to				sion Ra	tes from			\boxtimes		
		nic Equipment (ISO/I			AL-UZ 205							
P10.3	Typical emission rate (operation phase) is (mg/h):											
	Electrophotographic devices: Ozone <0.3 (LOQ) Dust <0.22 (LOQ) Styrene 0.146 Benzene <0.012 (LOQ) TVOC 5.005							\Box				
	Ink dev	ces:	Dus	st	Styrene		Benzene	-	TVOC			
	Note: c	ompliance with maxin	num emission rates	in eco labels	to be decla	red in P	14.					
P11		nable materials for										
P11.1*	A Safet	y Data Sheet (SDS) i	s available for the in	k/toner prep	aration, ever	n if not le	egally requ	uired (se	e P4.3).			
P11.2*	Paper 6 EN 122	containing post-cons 81.	umer recycled fiber	s can be us	sed, provide	d that i	t meets tl	he requi	rements c			
P11.3*	2-sided	(duplex) printing/cop	ying is an integrated	product fun	ction.					\boxtimes		
P11.4*	The pro	duct is delivered to e	nd-user with default	auto-duplex	enabled.						$\overline{\Box}$	$\overline{\Box}$
P13	Packag	ing and documenta	tion							_		
P13.1*	Produc Produc	packaging material packaging material packaging material packaging material ded Polyethelyne 0.03 kg	type(s): <i>Plastic - HD</i> type(s): <i>Expanded I</i>	PE	weight (kg):	0.10 eight (ko	g): 0 .23					
P13.2*	Produc	plastic primary pack	aging is free from P\	/C.						\boxtimes		
P13.3*		duct primary corruga er recovered fiber co	ated fiberboard pack entent: Recycled	kaging, spec content >2	cify the cont	ained p	ercentage	of mini	mum post	t-		
P13.4*		media for user and phic \boxtimes , Paper \boxtimes , O		on (tick box):								
P13.5	(Please	only complete this it	em if paper docume	ntation used)							
		d product documenta blease specify:	ation on paper media	a is chlorine-	free:							
	Totally	chlorine-free								\boxtimes		
	Elemen	tal chlorine-free								Ħ		
	Process	sed chlorine-free								Ħ		
P14	Volunta	ary programs:										
P14.1		duct meets the requi	rements of the follow	ving voluntar	y program(s	;):						
		Y STAR® el: <i>Blue Angel</i>	Criteria version: R			2017	Product printing	category functio				
P15		nal information (Se	Criteria version:		Date:		Product	category	/.			
. 10		he battery containe		ict should h	e disposed	of pror	erly with	the pro	duct. The	product	is	
	proper P2.3 - 1 the cus	y labeled with the W The battery containe tomer; however, is The packaging materia	NEEE disposal sym ed within this produ designed for easy	nbol and ins nct meets th removal by	tructions for e exception recyclers a	or such n listed. nd serv	disposal The batt rice provid	is listed ery is n ders.	in the pro ot intende	oduct Use ed to be re	er's G emove	
	they are	>25g										
	P7.14 -	A small amount of bro	omine may be presen	nt in covers d	ue to sourcin	g post-c	onsumer r	ecycled	content. N	lo bromine	was	ļ

P10.3 - CS521dn model used in emissions testing for this family

intentionally added in the processing of these parts.

P7.20 - Per IEEE 1680.2 PCR calculation

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1