

Ecma/TC38-TG3/2015/025 (Rev. 1 - 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lexmark	Logo	
Company name *	Lexmark International,		тм
Contact information *	Troy Foster (USA)		Lexmark
e-mail address	Email: Sustainability@lexmark.com		LCAHOR
Internet site *	www.lexmark.com/TED and csr.lexmark.com		
Additional information			

The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statements given in this declaration.						
Type of product *	Multi-Function Monochrome laser devices					
Commercial name *	.exmark MB2236adwe					
Model number *	1B2236adwe					
Issue date *	20 May 2021					
Intended market *	🛛 Global 🔄 Europe 🔄 Asia, Pacific & Japan 🔄 Americas 📃 Other					
Additional information	Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

mouerm	umber *	MB2236adwe	Logo			11
Issue date *		20 May 2021		Le:	×m	ark
Produc	t environ	mental attributes - Legal requirements		Require	ement	met
Item		Yes	No	n.a.		
P1		bus substances and preparations				
P1.1*		do comply with the current European RoHS Directive. (See legal reference and No	DIE B1)		Ц	
P1.2*	Commer	o do not contain Asbestos (see legal reference). ht: Legal reference has no maximum concentration value.				
P1.3*	hydrobro trichloroe	a do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), proofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetracl ethane, methyl bromide (see legal reference). Comment: Legal reference has no n ration values.				
P1.4*		o do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych (I (PCT) in preparations (see legal reference).	lorinated	\boxtimes		
P1.5*		o do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carl ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	oon atoms in th	ie 🔀		
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.					
P1.7*	REACH sustaina	Article 33 information about substances in articles is available at (add URL or mail ability@lexmark.com	contact):	\times		
P2	Batterie	S				
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)					
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)					
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		\times		
P3	Conform	nity verification & Eco design (ErP)				
P3.1*	The Dec	luct is CE-marked to show conformance with applicable legal requirements (see leg laration of Conformity can be requested at (add link or e-mail address): cmark.com/regulatory	gal reference).	\boxtimes		
P3.2*		luct complies with the Eco design requirements for energy-related products, al reference).		\boxtimes		
		d information is; given in item P15 or added to this document,		\times		
		available at (add URL): www.lexmark.com/regulatory				
P4	Consum	hable materials				
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1).	ax 0,01% (see	\boxtimes		
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0,1% by weight (see leg	al reference).	\times		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).					
P5		packaging				
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercury ant chromium by weight of these together.	y, cadmium a	nd 🔀		
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of e legal reference).	of the material	(s) 🔀		
P5.3*	The prod (see lega	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.				
P6	Treatme	nt information				
		on for recyclers/treatment facilities is available (see legal reference).		X	_	

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model n	umber *	MB2236adwe Logo				756
Issue da	ate *	20 May 2021		Le	xm	ark
	Environn	mental attributes - Market requirements (See General NOTE GN below) nental conscious design	Re	-	ment	
Item		tory to fill in. Additional information regarding each item may be found under P14.		Yes	No n	.a.
P7	Design	mbly requeling				
P7.1*		mbly, recycling t have to be treated separately are easily separable				
P7.2*		aterials in covers/housing have no surface coating.		\mathbf{X}	<u>+</u>	<u> </u>
P7.3*					<u> </u>	╞
		arts > 100 g consist of one material or of easily separable materials.			<u> </u>	╞
P7.4*	-	arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	4		<u> </u>	<u> </u>
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available	toois.		<u>H</u>	<u> </u>
P7.6*	Labels at Product	re easily separable. (This requirement does not apply to safety/regulatory labels).		\bowtie		
P7.7*		g can be done e.g. with processor, memory, cards or drives		<u> </u>	\square	
P7.8*				<u> </u>		
P7.9.		ig can be done using commonly available tools ints are available after end of production for: 5 years			<u>+</u>	<u> </u>
P7.10					<u>-</u>	<u> </u>
F7.10		s available after end of production for: 5 years and substance requirements		\mathbf{X}		
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):				
		type: <i>plastics</i> Material type: Material type:				
P7.12	Insulatio	n materials of external electrical cables are PVC free.			\times	
P7.13	Insulatio	n materials of internal electrical cables are PVC free.		$\overline{\Box}$	\square	
1 7.14 2	(1000 pp chloride c	tic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1 m) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing r t-consumer recycled content.	l polyvinyl			
P7.15		ircuit boards, PCBs (without components) are low halogen: all 🗌 PCBs > 25 g 🗌 are low ed in IEC 61249-2-21. (See NOTE B2)	v halogen		\times	
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:					
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without compone additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS				
	according	nemical specifications of flame retardants in printed circuit boards (without components) > 2 g ISO 1043-4: <i>FR16</i>	-	\boxtimes		
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances/prepar ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	ations in			
	Alt. 2: CH	nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR1	16/17/30/40			
P7.19	In plastic assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which have be the following Risk phrases; and Hazard statements: ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE I	en			
P7.20*	If YES; a a) Of t perc or	sumer recycled plastic material content is used in the product (See NOTE B6): t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calcul centage of total plastic by weight) is %. weight of recycled material is g.	ated as a			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine whichare included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nu	nber *	MB2236a	dwe			Logo		
Issue date	*	20 May 20	y 2021 💽 Lex					
Product	Product environmental attributes - Market requirements (continued) Requirement me							
Item Yes No n.a.								
Material and substance requirements (continued)								
P7.21*	If YES; a a) Of t tota or	at least one total plastic al plastic by		below shall be an the biobased plast		ated as a percenta	ge of	
P7.22*			ee from mercury, i.e. le pecify: Number of lam		np. kimum mercury content pe	er lamp: mg		
P8	Batterie	-						
P8.1*			mposition: Lithium ma	anganese				
P9			ion (See NOTE B8)					
P9.1	For the p	product the	following power levels	or energy consum	ptions are reported:			
Energy mo	ode *		Power level at 100 V AC	Power level a 115 V AC	t Power level at 230 V AC	Reference/Stand modes and test		
Sleep moo STAR® Or (OM) prod	perational		W	W	W			
Standby/or ENERGY Mode (OM	STAR Ope	erational	W	W	W			
	TEC value for ENERGY STAR TEC products		kWh/week	0.53 kWh/week	0.53 kWh/week	Energy Star V3	.0	
Ready		33	W	5.75 W	5.58 W	Corporate Stan	dard 🗌	
Sleep			W	1.061 W	1.045 W	Energy Star V3	.0	
Off			W	0.078 W	0.179 W	Energy Star V3	.0	
Printing			W	448 W	451 W	Corporate Stan		
Сору			W	438 W	415 W	Corporate Stan	dard 🗌	
			W	W	W			
External P	ower Supp	oly Efficienc	cy Level (International	Efficiency Marking	Protocol) * :		\square	
Print/Scan	Speed *	:	34 images per minute					
Default tim	e to enter	energy sav	ve mode: 15 minutes			Energy Star V3	.0	
P9.2*								
P10	Emissio							
			Declared according to	ISO 9296 (See NC				
P10.1	Mode	M	lode description		Statistical upper limit A-v L _{WA,c} (B)	veighted sound pov	ver level,	
	Idle * Idle / Ready / Sleep / Hibernate * 3.1							
	Operation * Simplex Monochrome Printing * 6.7							
	Other m		Duplex Monochrome	-	6.4			
	Measured according to: X ISO 7779 ECMA-74 Other (only if not covered by ECMA-74)							

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	mber *	MB2236adwe				Logo				
Issue date *		20 May 2021					Lexmo		٦rk	
Product	environ	mental attribute	es - Market requirements (continued)			F	Require	ment	t me
ltem								Yes	No	n.a.
	Chemi	cal emissions from	n printing products (See NOT	E B10)						
P10.2*	•	0	to ECMA-328 Determination of 0) , other specify: <i>DE-UZ 20</i>		n Rates from El	ectronic		\boxtimes		
P10.3	Typical	emission rate (ope	ration phase) is (mg/h):							
	Electro Ink dev	• •	es: Ozone <0.23 Dust 0.84 Dust	Styrene 0.06 Be Styrene	nzene 0.016 T∖ Benzene	/OC <mark>5.635</mark> TVOC				
			ximum emission rates in eco la	bels to be declared	l in P14.					
P11	Consu	mable materials fo	or printing products							
P11.1*	A Safet	y Data Sheet (SDS) is available for the ink/toner p	reparation, even if	not legally requ	ired (see P	4.3).	\times		
P11.2*	Paper EN 122	01	nsumer recycled fibers can be	e used, provided	that it meets th	e requiren	nents of	\boxtimes		
P11.3*	2-sided	(duplex) printing/c	opying is an integrated product	function.				\boxtimes		
P11.4*	The product is delivered to end-user with default auto-duplex enabled.									
P13	Packaging and documentation									
P13.1*	Produc		al type(s): <i>Corrugated Carton</i> al type(s): <i>Corrugated Carton</i> al type(s): weigh	weight (kg): 1.		}				
P13.2*	Product plastic primary packaging is free from PVC.									
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post- consumer recovered fiber content: 25 %									
P13.4*		media for user and ic 🛛, Paper 🔀	l product documentation (tick b Other	ox):						
P13.5	(Please only complete this item if paper documentation used) User and product documentation on paper media is chlorine-free:									
	Totally chlorine-free									
	Elemental chlorine-free									
	Processed chlorine-free									
P14		ary programs:								
P14.1			uirements of the following volu	ntary program(s):						
	•	GY STAR®	Criteria version: V3.0	Date:	Product	category: /	maning	Fauinme	ont	
	Eco-lab Eco-lab	el:	Criteria version: Criteria version:	Date: Date: Date:	Product	category: n category: category:	maying	_quipine		
P15		nal information (Date.	FIUUUCL	calegory.				
115	Auditic									

NOTE B10 A Guidance document on Chemical Emissions is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037 / 2000 , 2038 / 2000 , 2039/ 2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013 / 56 / EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801 / 2013 amending Regulation (EC) No 1275/ 2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907 / 2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1