



Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lexmark	Logo	
Company name *	Lexmark International,		TM
Contact information * e-mail address	Troy Foster sustainability@lexmark.com		Lexmark
Internet site *	www.lexmark.se		
Additional information			

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multi-Function Monochrome laser devices			
Commercial name *	Lexmark MB2236adw, MB2236i			
Model number *	MB2236adw, MB2236i			
Issue date *	15 April 2019 (updated 30 September 2021)			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Model number *		MB2236adw, MB2236i	Logo			■ TM		
Issue date *		15 April 2019 (updated 30 September 2021)		Le	×m	ark		
Product	roduct environmental attributes - Legal requirements					met		
Item				Yes	No	n.a.		
P1		ous substances and preparations s do comply with the current European RoHS Directive. (See legal reference and NC	TE D ()	<u> </u>	_			
P1.1*		DIE B1)	X	<u>Н</u>				
P1.2*	Products Commer		X	Ш				
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m ration values.						
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlor) in preparations (see legal reference).						
P1.5*	Products chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	on atoms in the					
P1.6*	(see lega	th direct and prolonged skin contact do not release nickel in concentrations above 0, al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	5 μg/cm²/week					
P1.7*		Article 33 information about substances in articles is available at (add URL or mail cability@lexmark.com	contact):	X				
P2	Batterie	s						
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the Information on proper disposal is provided in user manual. (See legal reference)	ne disposal	\boxtimes				
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)							
P2.3*	Batteries	s and accumulators are readily removable. (See legal reference)		\boxtimes				
P3	Conformity verification & Eco design (ErP)							
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address): www.lexmark.com/regulatory							
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference).							
	Required information is; given in item P15 or added to this document, given in item P15 or added to this document, available at (add URL): www.lexmark.com/regulatory							
P4	Consun	nable materials						
P4.1*		o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1).	x 0,01% (see					
P4.2*	_	er is used in the product, it does not contain cadmium max 0,1% by weight (see legal	al reference).	\boxtimes				
P4.3*	If the ink are Com applicab (see lega	/toner formulation/preparation is classified as hazardous or contains a substance for munity workplace exposure limits, the product/packaging is adequately labeled accule regulations and a Safety Data Sheet (SDS) in accordance with these requirement al reference).	r which there ording to					
P5		packaging	a a alma is construction	X	_			
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together.							
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature o ee legal reference).		\boxtimes				
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.							
P6	Treatment information							
P6.1*	Informati	ion for recyclers/treatment facilities is available (see legal reference).						

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

lodel number *	MB2236adw. MB2236i	Logo	756
ssue date *	15 April 2019 (updated 30 September 2021)		Lexmark

	t environmental attributes - Market requirements (See General NOTE GN below) Environmental conscious design	Require	ement	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes No n.a.		
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	\times		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\times		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives		\times	
P7.8*	Upgrading can be done using commonly available tools			\boxtimes
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: Material type: Material type:			
P7.12	Insulation materials of external electrical cables are PVC free.		\times	
P7.13	Insulation materials of internal electrical cables are PVC free.		X	
	kternal plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.			
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See NOTE B2)		\times	
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):			
	TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:			
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: FR16			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR16/17/30/4	10		
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is %. or b) The weight of recycled material is g.			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine whichare included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nur	mber *	MB2236a	dw, MB2236i		Logo	79			
Issue date	e *	15 April 2	2019 (updated 30 Sep	tember 2021)		Lexmark			
			al attailmates. Manket no mainements (o antimus d)						
· · · ·							Requirement met		
Item	Item Yes No n.a.								
P7.21*	Material and substance requirements (continued) P7.21* Biobased plastic material content is used in the product (See NOTE B7):								
	If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of								
			parts' weight > 25 g, weight) is %.	the biobased plast	ic material content (calcul	lated as a percentage	· of		
	or	plastic by	weight) is 70.						
	b) The	weight of	the biobased plastic m	aterial is g.					
P7.22*	Light cou	roop oro fr	ee from mercury, i.e. le	oos than 0.1 mg/lan	nn.				
F1.22			pecify: Number of lam		rip. ximum mercury content pe	er lamp: mg			
P8	Batteries								
P8.1*			mposition: Lithium ma	anganese					
P9			ion (See NOTE B8)						
P9.1			following power levels	or energy consum	ptions are reported:				
Energy mo	ode *		Power level at	Power level at	t Power level at	Reference/Standar	rd for energy		
			100 V AC	115 V AC	230 V AC	modes and test me	ethod *		
	de for ENE		W	W	W				
(OM) prod	perational N ucts	/lode							
Standby/of	ff mode for		W	W	W		\boxtimes		
ENERGY STAR Operational		rational							
Mode (OM) products TEC value for ENERGY STAR		GY STAR	kWh/week	0.54 kWh/week	0.56 kWh/week	Energy Star V3.0			
TEC products									
(TEC= Typ	oical Energy	/							
Ready			W	5.23 W	5.11 W	Corporate Standa	ard		
Sleep			W	1.19 W	1.23 W	Energy Star V3.0			
Off			W	0.03 W	0.06 W	Energy Star V3.0			
Printing			W	454 W	454 W	Corporate Standa	ard		
Copying			W	428 W	421 W	Corporate Standa	ard 🔲		
			W	W	W				
External P	ower Supp	y Efficiend	cy Level (International	Efficiency Marking	Protocol) *:				
Print/Scan	Print/Scan Speed * : 34 images per minute								
Default tim	ne to enter e	energy sav	ve mode: 15 minutes			Energy Star V3.0			
P9.2*	Information	on about th	ne energy save function	n is provided with tl	he product.	-			
P10									
D. ()	Noise emission – Declared according to ISO 9296 (See NOTE B9)								
P10.1	Mode Mode description Statistical upper limit A-weighted sound power level, $L_{WA,c}$ (B)				· level,				
	Idle * Idle / Ready / Sleep / Hibernate * 3.1								
	Operation		Simplex Monochrom		* 6.7				
Other mode									
	Measured according to: 🔀 ISO 7779 🔀 ECMA-74								
			Other	(only if not covered	d by ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model number *		MB2236adw, MB22	?36i				Logo				714
Issue date *		15 April 2019 (updated 30 September 2021)						Lexmark			
Product	environ	mental attributes	- Market requiremen	ts (con	tinued)				Require	ment	met
Item									Yes	No	n.a.
		•	orinting products (See I								
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic Equipment (ISO/IEC 28360), other specify: DE-UZ 205										
P10.3	Typical emission rate (operation phase) is (mg/h):										
	Electrop	hotographic devices:	: Ozone <0,23 Dust 0,8	4 Styr	ene 0,06 Be	enzene <mark>0,0</mark> 1	6 TVOC 5,	635			
	Ink devi	ces:	Dust	S	tyrene	Benzene	e TV	OC			\boxtimes
	Note: co	ompliance with maxim	num emission rates in ec	o labels	to be declare	d in P14.					
P11		nable materials for									
P11.1*	A Safety	/ Data Sheet (SDS) is	s available for the ink/ton	er prepa	ration, even i	f not legally	required (se	ee P4.3).	X		
P11.2*	Paper of EN 122		umer recycled fibers ca	n be us	ed, provided	that it mee	ets the requ	irements of	X		
P11.3*	2-sided	(duplex) printing/copy	ying is an integrated prod	duct func	tion.				\boxtimes		
P11.4*	The pro	duct is delivered to er	nd-user with default auto	-duplex e	enabled.				\times		
P13	Packaging and documentation										
P13.1*	Product packaging material type(s): Corrugated Carton (Kraft paper) weight (kg): 1.23 Product packaging material type(s): Corrugated Carton weight (kg): 1.3 Product packaging material type(s): weight (kg):										
P13.2*	Product plastic primary packaging is free from PVC.										
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content: 25 %										
P13.4*	Specify media for user and product documentation (tick box): Electronic , Paper , Other										
P13.5		•	em if paper documentation	,							
	User and product documentation on paper media is chlorine-free:										
	Totally chlorine-free										
	Elemental chlorine-free										
		sed chlorine-free									
P14		ary programs:									
P14.1	•	•	ements of the following v	voluntary	,						
	ENERG Eco-lab Eco-lab		Criteria version: <i>V3.0</i> Criteria version: Criteria version:		Date: Oct 2 Date: Date:	Pro	duct catego duct catego duct catego	ry:	Equipme	ent	
P15	Additional information (See NOTE B11)										
			,								

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037 / 2000 , 2038 / 2000 , 2039/ 2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013 / 56 / EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801 / 2013 amending Regulation (EC) No 1275/ 2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907 / 2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1