

## Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                                 | Lexmark   | Logo    |
|---|---|---------|
| Company name *                          | Lexmark International Inc.  |         |
| Contact information *<br>e-mail address | Reyjoseph Ocaba<br>Lexmark International Inc.<br>740 New Circle Road, Building 001<br>Lexington, KY 40550<br>sustainability@lexmark.com | Lexmark |
| Internet site *                         | www.lexmark.com/TED - and- csr.lexmark.com  |         |
| Additional information                  |   |         |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Type of product *  | Multi-function Color Laser Device                            |  |  |  |  |  |
| Commercial name *  | Lexmark CX942adse, Lexmark XC9445                            |  |  |  |  |  |
| Model number *   | CX942adse, XC9445  |  |  |  |  |  |
| Issue date *   | 10 June 2022   |  |  |  |  |  |
| Intended market *  | 🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other |  |  |  |  |  |
| Additional information   |  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

## About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

Annex B1 of ECMA-370 6<sup>th</sup> edition, corrigendum December 2019 Page 1 (8)

| Model numb   | * CX942adse, XC9445 | Logo |         |
|--------------|---------------------|------|---------|
| Issue date * | 10 June 2022        |      | Lexmark |

5

|        | t environmental attributes - Legal requirements  | Require     |    | t met |
|--------|--|-------------|----|-------|
| Item   |  | Yes         | No | n.a.  |
| P1     | Hazardous substances and preparations  |             |    |       |
| P1.1*  | Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)   | $\boxtimes$ |    |       |
| P1.2*  | Products do not contain Asbestos (see legal reference).  | $\boxtimes$ |    |       |
|        | Comment: Legal reference has no maximum concentration value.   |             |    |       |
| P1.3*  | Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),   | $\boxtimes$ |    |       |
|        | hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-  |             |    |       |
|        | trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum<br>concentration values.  |             |    |       |
| P1.4*  | Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated   | $\boxtimes$ |    |       |
| F 1.4  | terphenyl (PCT) in preparations (see legal reference).   |             |    |       |
| P1.5*  | Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the   | $\square$   |    |       |
|        | chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).  |             |    |       |
| P1.6*  | Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 µg/cm²/week   | $\boxtimes$ |    |       |
|        | (see legal reference).   |             |    |       |
|        | Comment: Max limit in legal reference when tested according to EN1811:2011-5.  |             |    |       |
| P1.7*  | REACH Article 33 information about substances in articles is available at (add URL or mail contact):   | $\boxtimes$ |    |       |
|        | REACH Program Manager (Sustainability@lexmark.com); Corporate Sustainability Department, 740 West New Circle Rd., Lexington, KY 40550  |             |    | _     |
| P2     | Batteries  |             |    |       |
| P2.1*  | If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal  | $\square$   |    |       |
|        | symbol. Information on proper disposal is provided in user manual. (See legal reference)   |             |    |       |
| P2.2*  | Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal   | $\times$    |    |       |
|        | reference)   |             |    |       |
| P2.3*  | Batteries and accumulators are readily removable. (See legal reference)  | $\boxtimes$ |    |       |
| P3     | Conformity verification & Eco design (ErP)   |             |    |       |
| P3.1*  | The product is CE-marked to show conformance with applicable legal requirements (see legal reference).   | $\boxtimes$ |    |       |
|        | The Declaration of Conformity can be requested at (add link or e-mail address):  |             |    |       |
| P3.2*  | http://www.lexmark.com/en_us/about/regulatory-compliance/european-union-declaration-of-conformity.html The product complies with the applicable Eco design Requirements for Energy-Related Products. | $\square$   |    |       |
| 1 0.2  | (see legal reference).   |             |    |       |
|        | Required information is: a given in item P15 or added to this document.  | $\square$   |    |       |
|        | available at (add URL): https://csr.lexmark.com/product-certifications.php   |             |    |       |
| P4     | Consumable materials   |             |    |       |
| P4.1*  | If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium at a level greater  | $\square$   |    |       |
| F 4. I | than 0,01% (see legal reference and NOTE B1).  |             |    |       |
| P4.2*  | If ink/toner is used in the product, it does not contain cadmium at a level greater than 0,1% by weight (see   | $\boxtimes$ |    |       |
|        | legal reference)   |             |    |       |
| P4.3*  | If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there  | $\square$   |    |       |
|        | are Community workplace exposure limits, the product/packaging is adequately labeled according to  |             |    |       |
|        | applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available  |             |    |       |
|        | (see legal reference).   |             |    |       |
| P5     | Product packaging  |             |    |       |
| P5.1*  | Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and   | $\boxtimes$ |    |       |
| P5.2*  | hexavalent chromium by weight of these together.<br>The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)                                       |             |    |       |
| r'0.2  | used (see legal reference).  | $\boxtimes$ |    |       |
| P5.3*  | The product packaging material is free from ozone depleting substances as specified in the Montreal  | $\square$   |    |       |
| 1 0.0  | Protocol (see legal reference).  | $\bowtie$   |    |       |
|        | Comment: Legal reference has no maximum concentration values.  |             |    |       |
|        |  |             |    |       |
| P6     | Treatment information  |             |    |       |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number * Issue date * |  | CX942adse, XC9445 Logo   |           |           |      |  |
|-----------------------------|--|--|-----------|-----------|------|--|
|                             |  | 10 June 2022   |           | exm       | nark |  |
|                             |  | mental attributes - Market requirements (See General Note GN below)  |           |           |      |  |
|                             |  | nental conscious design  |           | rement    |      |  |
| Item<br>P7                  | *=manda<br>Design  | tory to fill in. Additional information regarding each item may be found under P14.  | Yes       | No n.     | a.   |  |
|                             | ¥  | nbly, recycling  |           |           |      |  |
| P7.1*                       |  | t have to be treated separately are easily separable   |           |           |      |  |
| P7.2*                       | Plastic m  | aterials in covers/housing have no surface coating.  |           | Ħ         |      |  |
| P7.3*                       | Plastic pa   | arts > 100 g consist of one material or of easily separable materials.   |           | Ħ         | H    |  |
| P7.4*                       | •  | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   |           | H         | - 2  |  |
| P7.5                        | •  | arts are free from metal inlays or have inlays that can be removed with commonly available tools.  |           | H         | H    |  |
| P7.6*                       | •  | e easily separable. (This requirement does not apply to safety/regulatory labels).   |           | H         | H    |  |
|                             | Product  |  |           |           |      |  |
| P7.7*                       |  | g can be done e.g. with processor, memory, cards or drives   | $\square$ |           |      |  |
| P7.8*                       | Upgradin   | g can be done using commonly available tools   |           | Ē         | Ē    |  |
| P7.9                        | Spare pa   | rts are available after end of production for: 5 years   |           |           | - H  |  |
| P7.10                       | Service is   | s available after end of production for: 5 years   |           |           |      |  |
|                             | Material   | and substance requirements   |           |           |      |  |
| P7.11*                      |  | cover/housing material type (e.g. plastics, metal, aluminum):  |           |           |      |  |
|                             |  | type: ABS Material type: PC+ABS Material type: HIPS  |           |           |      |  |
| P7.12                       |  | n materials of external electrical cables are PVC free.  |           | $\square$ |      |  |
| P7.13                       |  | n materials of internal electrical cables are PVC free.  |           |           |      |  |
| P7.14                       | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. |  |           |           |      |  |
| P7.15                       | Printed c<br>as define   | d in IEC 61249-2-21. (See NOTE B2)   | n 🗌       | $\square$ |      |  |
| P7.16                       | Marking:   |  | $\square$ |           |      |  |
| P7.17                       |  | emical specifications of flame retardants in printed circuit boards > 25 g (without components):<br>additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS #:   |           |           |      |  |
|                             |  | emical specifications of flame retardants in printed circuit boards (without components) > 25 g<br>g ISO 1043-4: <i>FR16</i>   |           |           |      |  |
| P7.18                       | <u>Alt. 1:</u> Fla<br>concentra<br>1. Chemi<br>2. Chemi  | ame retarded plastic parts > 25 g contain the following flame retardant substances/preparations i<br>ations above 0,1%:<br>cal name: , CAS #: (See NOTE B4)<br>cal name: , CAS #: "  | n         |           |      |  |
|                             | <u>Alt. 2: </u> Ch   | cal name: , CAS #: "<br>emical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:<br>R17, FR30+40  |           |           |      |  |
| P7.19                       | In plastic<br>assigned   | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been<br>the following Risk phrases; and Hazard statements:<br>ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5) |           |           |      |  |

NOTE B3 and B4 A Guidance document on Chemical substances is available;

see http://www.ecma-internationl.org/publications/standards/Ecma-370.htm.

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

| Issue date   | *  | 10.1                       |                                   |   |                                |                               |           |             | 19   |
|--|--|----------------------------|-----------------------------------|---|--------------------------------|-------------------------------|-----------|-------------|------|
| Product e  |  | 10 June                    | 2022                              |   |                                |                               | 🚺 Lex     | mo          | Irk  |
| Product e  |  |                            |                                   |   |                                |                               |           |             |      |
| 1 Iouuot e   | environm   | ental att                  | ributes - Market r                | equirements (conti  | nued)                          |                               | Require   |             | met  |
| Item   |  |                            |                                   |   |                                |                               | Yes       | No          | n.a. |
| P7.20*   |  |                            | ance requirements                 | · · · · ·   |                                |                               |           |             |      |
| P7.20  | Postcons   | umer recyc                 | cled plastic material o           | content is used in the p  | roduct (See NOTE B6)           | :                             | $\bowtie$ |             |      |
|  | If YES; at least one of the two alternatives below shall be answered;<br>a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a<br>percentage of total plastic by weight) is %. |                            |                                   |   |                                |                               |           |             |      |
|  | or   | entage of t                | otal plastic by weigh             | t) is %.  |                                |                               |           |             |      |
|  | b) The   | weight of r                | ecycled material is               | g.  |                                |                               |           |             |      |
| P7.21*   | Biobased   | plastic ma                 | terial content is used            | in the product (See N   | OTE B7):                       |                               |           | $\boxtimes$ |      |
|  | a) Of to<br>total<br>or  | otal plastic<br>plastic by | parts' weight > 25 g              | es below shall be answe<br>, the biobased plastic r<br>material is g. |                                | ated as a perce               | ntage of  |             |      |
| P7.22*   | Light sour   | ces are fre                |                                   | less than 0,1 mg/lamp.  | um mercury content pe          | er lamp: n                    | ng        |             |      |
| P8   | Batteries  |                            |                                   |   | -                              |                               | -         |             |      |
| P8.1*  | Battery ch   | iemical coi                | mposition: <i>Lithium I</i>       | Manganese Dioxide (L  | iMnO2)                         |                               |           |             |      |
| P9   |  |                            | on (See NOTE B8)                  |   |                                |                               | -         |             |      |
| P9.1   | For the pr   | oduct the                  | following power level             | s or energy consumption   | ons are reported:              |                               |           |             |      |
| Energy mo  | de *   |                            | Power level at<br><b>100</b> V AC | Power level at<br>115 V AC  | Power level at <b>230</b> V AC | Reference/Sta<br>modes and te |           | nergy       |      |
| Sleep mode<br>STAR® Op<br>(OM) produ   | perational N   |                            | W                                 | W   | W                              |                               |           |             |      |
| Standby/of<br>ENERGY S<br>Mode (OM)  | f mode for<br>STAR Oper  | ational                    | W                                 | W   | W                              |                               |           |             |      |
| TEC value<br>TEC produ<br>Energy Cor   | for ENERC  | Typical                    | 0.72 kWh/week                     | 0.71 kWh/week   | 0.73 kWh/week                  | Energy Star                   | V3.2      |             |      |
| Printing   |  |                            | 675 W                             | 672 W   | 697 W                          | Corporate St                  | andard    |             |      |
| Ready Mo   | de   |                            | <mark>81</mark> W                 | 76 W  | 94 W                           | Energy Star                   | V3.2      |             |      |
| Sleep  |  |                            | 1.17 W                            | 1.13 W  | 1.15 W                         | Energy Star                   | V3.2      |             |      |
| Hibernate  |  |                            | 0.04 W                            | 0.05 W  | 0.09 W                         | IEC 62301                     |           |             |      |
| Off  |  |                            | 0.02 W                            | 0.02 W  | 0.04 W                         | IEC 62301                     |           |             |      |
|  |  |                            | W                                 | W   | W                              |                               |           |             |      |
| External Po  | ower Suppl   | y Efficienc                | y Level (Internationa             | I Efficiency Marking Pr   | otocol) * :                    |                               |           |             |      |
| Print/Scan   | Speed *  | :                          | 45 images per minut               | e   |                                | ISO 24734                     |           |             |      |
| Default time to enter energy save mode: 15 minutes Energy Star V3.2            |  |                            |                                   |   |                                | V3.2                          |           |             |      |
| P9.2* Information about the energy save function is provided with the product. |  |                            |                                   |   |                                |                               |           |             |      |

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy efficiency is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

| Model number * | CX942adse, XC9445 | Logo |         |
|----------------|-------------------|------|---------|
| Issue date *   | 10 June 2022      |      | Lexmark |

| Product | t environmental a  | ttributes - Market requirement  | ts (continued)   |  | Require     | ment | met  |
|---------|--|---|--|--|-------------|------|------|
| Item    |  |   |  |  | Yes         | No   | n.a. |
| P10     | Emissions  |   |  |  |             |      |      |
| D40.4   |  | - Declared according to ISO 9296 (S   |  | line it A succion before the success of the success of |             |      |      |
| P10.1   | Mode   | Mode description  | Statistical upper $L_{WA,c}$ (B)                         | limit A-weighted sound power I                         | evel,       |      |      |
|         | Idle   | * Idle / Ready  | 4.5  |  |             |      |      |
|         | Operation  | * Duplex Monochrome Printing  | 6.7  |  |             |      |      |
|         | Other mode   | Simple Monochrome Printing  | 6.5  |  |             |      |      |
|         | Measured accordi   | ing to: 🔀 ISO 7779 🔀 ECMA-74  | (only if not covere                                      | d by ECMA-74)  |             |      |      |
|         | Chemical emissi  | ons from printing products (See I   |  |  |             |      |      |
| P10.2*  |  | ccording to ECMA-328 Determinatio   |  | Rates from Electronic                                  |             |      |      |
|         | •  | EC 28360) , other specify: <b>RAL-</b>  |  |  |             |      |      |
| P10.3   |  | rate (operation phase) is (mg/h):   |  |  |             |      |      |
|         | Electrophotograph<br>TVOC <mark>8.018</mark>   | nic devices: Ozone < <u>0.29 (LOQ)</u> Du   | st <0.24 (LOQ) Styrene                                   | 0.311 Benzene <0.012 (LOQ)                             |             |      |      |
|         | Ink devices:   | Dust  | Styrene E  | Benzene TVOC   |             |      |      |
|         | NOTE: compliance   | e with maximum emission rates in e  | co labels to be declared                                 | in P14   |             |      |      |
| P11     |  | terials for printing products   |  |  |             | ·    |      |
| P11.1*  |  | eet (SDS) is available for the ink/ton  | er preparation, even if n                                | ot legally required (see P4.3).                        | $\square$   |      |      |
| P11.2*  | Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of |   |  |  |             |      |      |
| P11.3*  |  | printing/copying is an integrated proc  | duct function.   |  | $\square$   |      |      |
| P11.4*  | The product is del   | livered to end-user with default auto   | -duplex enabled.   |  |             | Ħ    | Ħ    |
| P13     | Packaging and d  | locumentation   | -  |  |             |      |      |
| P13.1*  | Product packaging<br>Product packaging<br>Product packaging<br>Product packaging                       | g material type(s): we<br>g material type(s): we<br>g material type(s): we            | eight (kg):<br>eight (kg):<br>eight (kg):<br>eight (kg): |  |             |      |      |
| P13.2*  |  | imary packaging is free from PVC.   |  |  | $\square$   |      |      |
| P13.3*  | consumer recover   | ry corrugated fiberboard packaging,<br>red fiber content: %                           |  | ercentage of minimum post-                             |             |      |      |
| P13.4*  | Electronic 🔀, Pa   |   |  |  |             |      |      |
| P13.5   |  | plete this item if paper documentation<br>documentation on paper media is c<br>ecify: |  |  | $\boxtimes$ |      |      |
|         | Totally chlorine-fre   | 26  |  |  |             |      |      |
|         | Elemental chlorine   |   |  |  |             |      |      |
|         | Processed chlorin  |   |  |  | H           |      |      |
| P14     | Voluntary progra   |   |  |  |             |      |      |
| P14.1   |  | s the requirements of the following v   | voluntary program(s):                                    |  |             |      |      |
|         | ENERGY STAR®<br>Eco-label: <b>Blue A</b>   |   | Date: Nov. 202<br>IZ-219 Date: Jan. 202                  | <b>U</b>   |             |      | l    |
|         |  | •   |  | Printing Function                                      |             |      |      |

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm.

NOTE B10 A Guidance document on Chemical Emissions is available;

 $see \ \underline{http://www.ecma-international.org/publications/standards/Ecma-370.htm}.$ 

| Model number * | CX942adse, XC9445 | Logo | <b>1</b> <sup>10</sup> |
|----------------|-------------------|------|------------------------|
| Issue date *   | 10 June 2022      |      | Lexmark                |

| Produc | t environmental attributes - Market requirements (concluded) Requirement met   |
|--------|--|
| P15    | Additional information (See NOTE B11)  |
| P2.1   | The battery contained within this product should be disposed of properly with the product. The product is<br>properly labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide |
| P2.3   | The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers                            |
| P5.2   | The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used when they are >25g   |
| P7.14  | A small amount of bromine may be present in covers due to sourcing post-consumer recycled content. No bromine was intentionally added in the processing of these parts.  |
| P7.20  | Per IEEE 1680.2 PCR calculation  |

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B1

| Reference  | Declaration item             |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.   | P1.1, P3.1, P4.1             |
| Commission Regulation (EC) 1907/2006 (REACH<br>Regulation), annex XVII   | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Commission Regulation (EC) 1907/2006 (REACH<br>Regulation), annex VII  | P1.10                        |
| Commission Regulation (EC) 1907/2006 (REACH<br>Regulation), Article 31, annex II)  | P4.3                         |
| Commission Regulation (EC) No. 2037/2000,<br>2038/2000, 2039/2000, (Marketing and use of Ozone<br>layer depleting substances)  | P1.3, P5.3                   |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                         |
| Directive 2006/66/EC (Battery and accumulators<br>Directive), as amended.*<br>* These provisions shall not apply where, for safety,<br>performance, medical or data integrity reasons, continuity of<br>power supply is necessary and requires a permanent<br>connection between the appliance and the battery or<br>accumulator.              | P2.1, P2.2, P2.3, P8.1       |
| Directive 2014/35/EU (Low Voltage Directive)   | P3.1                         |
| Directive 2014/30/EU (EMC Directive)   | P3.1                         |
| Directive 2014/53/EU (RE Directive)  | P3.1                         |
| Commission Regulation (EC) No 1275/2008<br>implementing Directive 2005/32/EC of the European<br>Parliament and of the Council with regard to ecodesign<br>requirements for standby and off mode electric power<br>consumption of electrical and electronic household and<br>office equipment (Standby Regulation)                              | P3.1, P3.2, P9.1             |
| Commission Regulation (EC) 801/2013 amending<br>Regulation (EC) No 1275/2008 with regard to<br>ecodesign requirements for standby, off mode electric<br>power consumption of electrical and electronic<br>household and office equipment, and amending<br>Regulation (EC) No 642/2009 with regard to ecodesign<br>requirements for televisions |                              |
| Commission Regulation (EC) No 278/2009 of 6 April<br>2009 implementing Directive 2005/32/EC of the<br>European Parliament and of the Council with regard to<br>ecodesign requirements for no-load condition electric<br>power demand and average active efficiency of<br>external power supplies   | P3.1, P3.2, P9.1             |
| Commission Regulation (EC) 1272/2008 (CLP<br>Regulation)   | P4.3, P7.19                  |
| Directive 2004/12/EC (Packaging Directive)   | P5.1                         |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                         |

| Directive 2012/19/EU (WEEE directive)   | P6.1 |
|---|------|
| Implementing Regulation (EU) 2019/290 establishing<br>the format for registration and reporting of producers<br>of electrical and electronic equipment to the register.   |      |
| Commission Implementing Regulation 2017/699<br>establishing a common methodology for the calculation<br>of the weight of electrical and electronic equipment<br>(EEE) placed on the national market in each Member<br>State and a common methodology for the calculation of<br>the quantity of waste electrical and electronic<br>equipment (WEEE) generated by weight in each<br>Member State. |      |